

AMENDMENTS TO THE CLAIMS

The following listing of claims replaces all prior versions of the claims in the Application. With reference to the listing it is noted that, herewith, claims 43, 49, 54, and 57 are amended, and claims 48, 53, and 62 are canceled without prejudice or disclaimer. No new matter has been added.

Listing of Claims

Claims 1-42 (Canceled)

43. (Currently Amended) An apparatus comprising:

a processor;

a memory coupled to the processor and configured for storing data provided by the processor;

a splitting application configured to split received data including at least first image information and second image information into at least two data parts based on headers in the received data, wherein the first image information and the second image information are for displaying at least two substantially different images;

a wireless short-range transmitter coupled to the processor and configured to transmit at least one of the at least two data parts wirelessly to an external display device for displaying images corresponding to at least the first image information; and

a display coupled to the processor and configured for receiving at least one data part not transmitted by the wireless short-range transmitter and displaying images corresponding to at least the second image information,

wherein the images displayed on the external display device and the display coupled to the processor are substantially different.

44. (Previously Presented) An apparatus according to claim 43, further comprising a receiver for receiving a signal comprising data including at least the first image information and the second image information.

45. (Previously Presented) An apparatus according to claim 44,
wherein the receiver is a wide-area network receiver.

46. (Previously Presented) An apparatus according to claim 44,
wherein the memory comprises a buffer adapted to buffer the received signal to provide time for the splitting application to split the received data into the at least two parts.

47. (Previously Presented) An apparatus according to claim 43,
wherein the processor is configured to forward to the display coupled to the processor the at least one part of the received data that is not transmitted to the external display device.

Claim 48 (Canceled)

49. (Currently Amended) A method comprising:
obtaining data, including at least first image information and second image information,
in frames;

splitting the obtained data into at least two data parts based on headers in the obtained data, wherein the first image information and the second image information are for displaying at least two substantially different images; and

transmitting at least one of the at least two data parts wirelessly to an external display device for displaying images corresponding to at least the first image information,

wherein a coupled display is configured to receive at least one data part not transmitted wirelessly and display images corresponding to at least the second image information, and

wherein the images displayed on the external display device and the coupled display are substantially different.

50. (Previously Presented) A method according to claim 49,

wherein the obtained data is received from a receiver.

51. (Previously Presented) A method according to claim 50 further comprising:

buffering a received signal to provide time for a splitting application in a mobile terminal to split obtained data into the at least two parts.

52. (Previously Presented) A method according to claim 49 further comprising:

forwarding to a display of a mobile terminal a part of the split data that is not transmitted to the external display device.

Claim 53 (Canceled)

54. (Currently Amended) An article of manufacture comprising a computer readable medium containing computer readable code, which when executed by a processor causes the processor to split data, including at least first image information and second image information, obtained by a mobile terminal into at least two data parts based on headers in the data, wherein the first image information and the second image information are for displaying at least two substantially different images and transmit at least one of the at least two data parts wirelessly to an external display device for displaying images corresponding to at least the first image information, wherein a coupled display is configured to receive at least one data part not transmitted wirelessly and display images corresponding to at least the second image information, and wherein the images displayed on the external display device and the coupled display are substantially different.

55. (Previously Presented) The article of manufacture of claim 54, wherein the obtained data is received from a receiver.

56. (Previously Presented) The article of manufacture of claim 55, wherein the computer readable code further causes the processor to buffer a received signal to provide time for splitting of the obtained data into the at least two parts.

57. (Currently Amended) A system comprising a mobile terminal and an external display device, wherein the mobile terminal comprises a processor; a memory coupled to the processor and configured for storing data provided by the processor; a splitting application configured to split received data including at least first image information and second image information into

at least two data parts based on headers in the received data, wherein the first image information and the second image information are for displaying at least two substantially different images; a wireless short-range transmitter coupled to the processor and configured to transmit at least one of the at least two data parts wirelessly to an external display device for displaying images corresponding to at least the first image information; and a display coupled to the processor and configured for receiving at least one data part not transmitted by the wireless short-range transmitter and displaying images corresponding to at least the second image information, wherein the images displayed on the external display device and the display coupled to the processor are substantially different.

58. (Previously Presented) A system according to claim 57, further comprising a receiver for receiving a signal comprising data including at least the first image information and the second image information.

59. (Previously Presented) A mobile terminal according to claim 58, wherein the receiver is a wide-area network receiver.

60. (Previously Presented) A system according to claim 58, wherein the memory comprises a buffer adapted to buffer the received signal to provide time for the splitting application to split the received data into the at least two parts.

61. (Previously Presented) A system according to claim 57,

wherein the processor is configured to forward to the display coupled to the processor the at least one part of the received data that is not transmitted to the external display device.

Claim 62 (Canceled)